

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7601)

Set ¼ sec. post, from which
A Yew 12" dia., bears N.27°E., 68 lks.
A Yew 12" dia., bears S.52°W., 34 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7643)

A Granite rock in place 8x24x18 ins. above ground for ¼ sec. cor. I mark (X) at exact cor. point, ¼ on W. side, from which
A Madrone 8" dia., bears S.18½°E., 18 lks. dist. mkd. ¼ S27 BT.
A Madrone 12" dia., bears N.52°W., 70 lks. dist. mkd. ¼ S28 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-81

Found - Stone 8x24x18" above ground, ¼ W. face.
8" now 12" Laurel, S.18½°E., 11.9 ft., rotten center, faint scribe marks visible.
12" Laurel, now dead, N.52°W., 46.2 ft.
Set Brass cap on East edge of Corner stone, mkd.
County Surveyors Office
T 31 S R 2 W
¼ S 28 | S 27
1966
New BTs- 17" D.Fir N.75°W., 23.2 ft. mkd. ¼ S28 CS BT.
11" D.Fir N.41°E., 24.7 ft. mkd. ¼ S27 CS BT.