

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page 7602)

Set ¼ sec. post, from which
A Pine 24" dia., bears S.2°E., 97 lks.
A Pine 18" dia., bears S.5°W., 62 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7677)

The ¼ sec. cor. nearly obliterated. No trace is found of the post. One bearing tree has fallen and the other is deeply overgrown.
I reestablish the cor. in its original position as follows:
Set a basalt sone 15x12x6 ins., 10" in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 10" dia., bears N.30°E., 14 lks. dist. mkd. ¼ S22 BT
A Fir 10" dia., bears N.45°W., 9 lks. dist. mkd. ¼ S21 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 9, 1966 - C.S. File 54/28-74

Found - 10" Fir now snag, N.45°W., 5.9 ft., shows good scar
Orig. 40" Pine stump S.2°E., 64.0 ft., opened for scribe "¼".
No trace of NE. BT.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ S 21 | S 22
1966
New BTs- 22" D.Fir S.80½°E., 8.4 ft. mkd. ¼ S22 CS BT.
8" D.Fir N.8°W., 45.0 ft. mkd. ¼ S21 CS BT.

Survey by William Ruppert - For: U.S. Forest Service - Dec. 2, 1976 - C.S. file 58/136 and M 65-1

Found - 1966 DCSO brass cap, properly marked.
14" D.Fir, scribe visible, bears N.9°W., 45.0 ft.
20" D.Fir, stump, scribe visible, bears S.77 ¾°E., 8.2 ft.
10" snag, scar visible, bears N.43 ¾°W., 5.9 ft.
36" stump, deteriorated, bears S.02 ¾°E., 65.0 ft.
New BT - 14" Cedar scribed "T31S R2W ¼ S22 BT", LS 866 disk attached, bears S.52°E., 74.1 ft.