

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7602)

-----

Set post cor. secs. 15, 16, 21 and 22, from which  
 A Fir 18" dia., bears S.27°E., 68 lks.  
 A Laurel 18" dia., bears S.27°W., 58 lks.  
 A Laurel 10" dia., bears N.45°E., 40 lks.  
 A Cedar 24" dia., bears N.43°W., 31 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7676)

-----

The Sec. Cor., nearly obliterated. No trace of post. One bearing tree has fallen, marks on the other bearing tree, deeply overgrown. I reestablish the cor. in its original position as follows:  
 Set a serpentine stone 14x12x8 ins., 9½" in the ground marked with 3 notches on S. and E. edges, from which  
 A Cedar 30" dia., bears N.57°E., 67 lks. dist. mkd. T31S R2W S15 BT.  
 A Cedar 18" dia., bears S.20°E., 88 lks. dist. mkd. T31S R2W S22 BT.  
 A Madrone 24" dia., bears S.27°W., 59 lks. dist. mkd. T31S R2W S21 BT.  
 A Cedar 36" dia., bears N.43°W., 33 lks. dist. mkd. T31S R2W S16 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-59

-----

Found - 18" Fir, down, S.10°E., 44.8 ft., shows good scar.  
 24" Cedar stub, N.43°W., 20.5 ft., opened tree for scribe.

Set Brass cap at cor. mkd: County Surveyors Office

T	31	S	R	2	W
	S	16		S	15
	S	21		S	22
				1966	

New BTs- 9" Cedar N.4°E., 12.0 ft. mkd. T31S R2W S15 CS BT.  
 11" Cedar N.48°W., 14.4 ft. mkd. T31S R2W S16 CSBT  
 12" Cedar S.32°W., 26.6 ft. mkd. T31S R2W S21 CSBT  
 8" Cedar S.15°E., 14.6 ft. mkd. T31S R2W S22 CS BT

Survey by Glenn Baughman - For: U.S. Forest Service - Jan. 1975 - C.S. File 58/32-00C and M 56-6

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Found - 1966 DCSO brass cap for  $\frac{1}{4}$  corner.  
A 7" Cedar bears N.2°W., 12.0 ft. scribed T31S R2W S16 CS BT.  
An 8" Cedar bears N.47°W., 15.5 ft. scribed T31S R2W S16 CS BT.  
A 6" Cedar bears S.21°W., 15.2 ft. scribed T31S R2W visible.  
A 12" Cedar bears S.44°W., 33.1 ft. @ 18°30', scribed T31S R2W S21 CS BT.

The corner lies in recent slide. I leave the County brass cap out of position. I reestablish corner position by DCSO bearing trees which lie outside of the slide area, a 6" and 12" Cedar. Then I set two witness corners on South line between secs. 21 and 22 outside of active slide area.

Set 30" long, 2½" galv. I.P., 24" in the ground in a mound of stone with a 3" brass cap stamped: "T31S R2W WC S16 S15 S21 S22 OLS 536 1975". (247.03 ft. South of corner), from which

A Cedar 7" bears S.56°E., 9.8 ft. scribed "WC T31S R2W S22 BT" with brass washer stamped "CS 536" nailed at BT blaze.

A D.Fir 9" bears N.12°W., 9.0 ft. scribed "WC T31S R2W S21 BT" with brass washer stamped "CS 536" nailed at BT blaze.

Both trees have 6" red band painted around the tree corner. It lies on steep East slope approx. 100 ft. East of ridge top and 247 ft. South of draw.

Set 30" long, 2½" galv. I.P., 26" in the ground in a mound of stone with a 3" brass cap stamped: "T31S R2W WC 121.54 ft. S16 S15 S21 S22 OLS 536 1975". from which

A Cedar 10" bears S.79°E., 32.6 ft. scribed "WC T31S R2W S21 BT" with brass washer stamped "LS 536" nailed at BT blaze.

A Cedar 8" bears S.32°W., 29.3 ft. scribed WC T31S R2W S22 BT" with brass washer stamped LS 536" nailed at BT blaze.

Both trees have a 6" red band painted around tree. Corner lies 121 ft. South of draw and slide area.