

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7603)

Set ¼ sec. post, from which
 An Oak 12" dia., bears S.13°E., 60 lks.
 An Oak 12" dia., bears N.1°E., 76 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-57

Found - 1/2" Iron pipe, unrecorded.
 12" Oak, now 29", S.13°E., 39.6 ft., shows good scar. (Find dist. to be 41.0 ft.)
 12" Oak, now 30", N.1°W., 50.2 ft., (found dist. to be 51.2 ft.) Opened for scribing "¼S".
Set Brass cap at cor. mkd: County Surveyors Office
 T 31 S R 2 W
 ¼ S 16 | S 15
 1966
New BT - 12" D.Fir N.21°W., 28.0 ft. mkd. ¼ S16 CS BT.

Ray Wytcherly - For: Boise Cascade Corp.. - 10/2004 - M145-55

Found - 1966 DCSO brass cap from which original BTs
 An oak (29" dia. bears S.13°E., 41.0 ft.) Face healed over.
 An oak(30" dia. bears N.1°W., 51.2 ft.) Now dead.
 1966 DCSO BT: A D.Fir (12" dia. bears N.21°W., 28.0 ft.) face healed over.
New BTs- A D.Fir 9" dia. bears N.31°W., 24.50 ft. scribed "S16 ¼ BT"
 A D.Fir 7" dia. bears N.17°E., 44.73 ft. scribed "S15 ¼ BT"
 A D.Fir 9" dia. bears S.50°E., 14.03 ft. scribed "S15 ¼ BT"
 A D.Fir 10" dia. bears S.66°W., 17.59 ft. scribed "S16 ¼ BT"