

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7604)

Set post cor. secs. 3, 4, 9 and 10, from which
A Pine 18" dia., bears N.89°W., 350 lks.
A Pine 15" dia., bears S.75°W., 225 lks.
A Pine 15" dia., bears S.41°E., 350 lks.
A Pine 15" dia., bears N.34°E., 360 lks.
Built stone mound

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7682)

The Sec. Cor., which is nearly obliterated. The post is not found and the bearing trees are deeply overgrown. I re-establish the cor. in its original position as follows:
Set a serpentine stone 15x10x6 ins., 10" in the ground, marked with 5 notches on S. and 3 notches on E. edge, from which
A Yellow Pine 30" dia., bears N.34°E., 363 lks. dist. mkd. T31S R2W S3 BT.
A Yellow Pine 30" dia., bears S.44°E., 505 lks. dist. mkd. T31S R2W S10 BT.
No nearer trees available in secs. 3 and 10.
A Yellow Pine 30" dia., bears S.76°W., 226 lks. dist. mkd. T31S R2W S9 BT.
A Yellow Pine 36" dia., bears N.41½°W., 151 lks. dist. mkd. T31S R2W S4 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-64

Found - 36" Y.Pine now 53", N.41½°W., 99.7 ft., shows scar
30" Y.Pine, now dead, S.76°W., 149.2 ft., scribe visible "S9".
30" Y.Pine now 38", S.44°E., 332.0 ft., shows good scar.
30" Y.Pine, down & rotten, N.34°E., 239.0 ft. "BT" scribe.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
S 4 | S 3
S 9 | S 10
1966

New BTs- 30" Pine N.30°E., 281.0 ft. mkd. T31S R2W S3 CS BT.
14" dbl Pine, S.39½°W., 220.4 ft. T31S R2W S9 CS BT.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Survey by Glenn Baughman - For: U.S. Forest Service - March 1978 - M 65-69

-
- Found - 1966 DCSO brass cap.
54" Pine stump, bears N.41°30'W., 99.7 ft.
30" Pine, now down, bears S.76°W., 149.2 ft.
32" Pine, snag, bears S.44°E., 332.0 ft.
32" Pine bears N.30°E., 281.0 ft.
20" double Pine bears S.39°30'W., 220.4 ft.
10" Pine bears N.34°E., 239.6 ft., has been moved by a cat.
- New - 6" Pine bears N.48°W., 129.3 ft. scribed T31S R2W S4 BT.
5/8" x 30" Iron rod bears S.42°E., 21.9 ft.

BLM dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group No. 2071, surveyed April/May 2004 - (DCSO records Vol. 55 Page(s) 21379-80)

The cor. of secs. 3, 4, 9, & 10, perpetuated by Powell, in 1966, further perpetuated by Baughman, in 1978, monumented with an iron pipe, 1½" dia., firmly set, projecting 18" above the ground, with brass cap (properly) mkd. from which the remains of the orig. BTs reported by Mensch

A decayed pine snag, 37" dia., bears S.44°E., 331.0 ft., with scribe marks R2W visible on a partially open blaze. (Record 333.3 ft.)

A sawed and decayed pine stump, 22" dia., bears S.76°W., 147.4 ft., with fragmentary scribe marks visible on a partially healed blaze, alongside of which is the trunk, 18" dia., with no marks visible. (Record, 149.2 ft.)

and a bearing tree mkd. by Mensch

A decayed pine stump, size indeterminate, bears N.40½°W. 99.7 ft., with no marks visible. (Record, N.41½°W.)

and bearing trees mkd. by Powell

A pine, 34" dia., bears N.31½°E., 279.0 ft., with a healed blaze.

A pine, 19" dia., bears S.41¼°W., 220.3 ft., with a healed blaze.

and accessories mkd. by Baughman

A pine, 18" dia., bears N.48¾°W., 129.3 ft., with a healed double blaze.

An iron rod, 5/8" dia., bears S.41°E., 21.8 ft., firmly set, projecting 6" above the ground, with no cap.