

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6753)

-
- A Cedar 12" dia., for cor. secs. 3 & 4, 33 & 34, from which
 - A Fir 36" dia., bears N.70°W., 15 lks.
 - A Fir 15" dia., bears S.70°W., 12 lks.
 - A Fir 15" dia., bears S.20°E., 11 lks.
 - A Cedar 10" dia., bears N.89½°E., 73 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7686)

-
- The sec. cor. which is nearly obliterated, one bearing tree gone, the other bearing tree and cor. deeply overgrown. I reestablish the cor. in its original position as follows:
 The original cor. A Cedar 16" dia., for cor. of secs. 3, 4, 33 and 34, I remark T30S S34 on NE.; R2W S3 on SE.; T31S S4 on SW.; S33 on NW. side with 3 notches on E. and W. sides, from which
- A Fir 10" dia., bears N.62°E., 83 lks. dist. mkd. T30S R2W S34 BT.
 - A Fir 18" dia., bears S.20°E., 12 lks. dist. mkd. T31S R2W S3 BT.
 - A Fir 18" dia., bears S.70°W., 13 lks. dist. mkd. T31S R2W S4 BT.
 - A Fir 40" dia., bears N.70°W., 17 lks. dist. mkd. T30S R2W S33 BT.

Douglas Co. Surveyors Office - John M. Powell, & crew - Sept. 1966 - C.S. File 54/28-68

-
- Found 15" Corner tree, scribe visible "T30S S33-34", from which
- 10" D.Fir now 14", N.62°E., 54.0 ft., shows good scar.
 - 18" now 22" D.Fir, S.70°W., 8.6 ft., shows good scar.
 - 40" D.Fir N.70°W., 11.2 ft., scribe visible "T30S R1W S33"
 - 18" Fir, now stub, S.20°E., 7.9 ft.
- Set Brass cap on South side of corner tree mkd:
- | | | | | | |
|-------------------------|--------|--|------|-----|---|
| County Surveyors Office | | | | | |
| T 30 | S S 33 | | S 34 | R 2 | W |
| T 31 | S S 4 | | S 3 | | |
- 1966
- New BTs- 20" D.Fir S.10°E., 14.8 ft. mkd. T31S R2W S3 BT.
 - 8" Cedar N.35°W., 15.2 ft. mkd. T30S R2W S33 CS BT.

(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34, T30-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Glenn Baughman, PLS 536 - For: U.S. Forest Service
- March 1978 - M 65-69

Found - 1966 DCSO brass cap.
14" D.Fir bears N.62°E., 54.0 ft.
24" D.Fir bears S.70°W., 8.6 ft.
42" Fir bears N.70°W., 11.2 ft.
18" D.Fir bears S.20°E., 7.9 ft., snag.
20" D.Fir bears S.10°E., 14.8 ft.
8" Cedar bears N.35°W., 15.2 ft., now down.
15" Cedar corner tree.
New BT - 12" D.Fir bears N.12°W., 33.4 ft. scribed T30S R2W
S33 BT.

Survey by William Ruppert, LS #866 - For: U.S. Forest Service
April 1979 - M 70-61

Found - 20" Cedar corner tree. A 1" Pipe with 2½" brass cap
bears S.45°W., 1.3 ft. mkd. as per 1966.
24" stump, very rotten, S.35°52'E., 8.0 ft.
24" D.Fir, good face, S.6°22'E., 14.7 ft.
20" D.Fir, good face, S.68°32'W., 7.3 ft.
40" D.Fir, good face, N.66°35'W., 10.4 ft.
10" D.Fir, good face, N.9°09'W., 32.6 ft.
8" Cedar, windfall, N.36°09'W., 13.8 ft.
New BT - 18" D.Fir N.62°00'E., 43.3 ft. scribed T30S R2W S34
BT.

Gregory Lang - For: Phil Washburn, Roseburg Resources & Mark
Hubbard - July 1994 - M 120-69

Found - Brass Cap
17 3/4" Cedar Cor. Tree (turning snag)
18" Fir, bears N.62°E., 43.3' (1979)
21" Fir, bears S.68°32'W., 7.3'
42" Fir, bears N.66°35'W., 10.4'
Fir stump pile bears S.35°52'E., 8.0'
24" Fir, bears S.6°22'E., 14.7'
9" Cedar bears N.36°09'W., 13.8' (now down)
12" Fir, bears N.9°09'W., 32.6

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34, T30-2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

The cor. of secs. 3, 4, 33, & 34, on the N. bdy. of the Tp., perpetuated by Powell, in 1966, further perpetuated by Baughman, in 1978, further perpetuated by Ruppert, in 1979, monumented with the original cor. tree, a cedar, 16" dia., with fragmentary scribe marks visible on partially healed blazes on NE & NW faces, and healed blazes on SE & SW faces, from which the remains of the original bearing trees

A cedar, 19" dia., bears N.89½°E., 48.2 ft., with axe marks visible.

A decayed fir stump, size indeterminate, bears S.32½°E., 7.3 ft., with no marks remaining. (Record, S.20°E.) and the remains of the original BTs reported by Mensch

A fir, 21" dia., bears S.70°W., 8.6 ft., with a healed double blaze.

A fir snag, 31" dia., bears N.70°W., 11.2 ft., with no marks visible.

and the bearing tree mkd. by Mensch

A fir, 20" dia., bears N.62°E., 54.8 ft., with a healed blaze.

and the remains of bearing trees mkd. by Powell

A fir, 24" dia., bears S.5°E., 14.7 ft., with a healed double blaze.

A down and decayed cedar, 6" dia., bears N.37½°W., 14.2 ft., with scribe marks T30S R2W S33 BT visible on an open double blaze.

and a bearing tree mkd. by Baughman

A fir, 13" dia., bears N.9½°W., 32.5 ft., with a healed double blaze.

and new accessory

A stainless steel post, 28" long, 2½" dia., set 21" in the ground for a reference monument, bears S.15°14'11"W., 8.95 ft., with brass cap mkd. RM T31S R2W S4 8.9 FT. TO COR. 2004 and an arrow pointing to the corner.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description