

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 402300

PRIMARY CORNER DESCRIPTION C.C. for Secs. 27 & 28 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7643)

At a point 1.67 chs. East of the cor. of secs. 21, 22, 27 and 28. Point for closing cor. of secs. 27 and 28 falls on a serpentine rock in place, 12x24x16 ins. above ground on which I Cut a cross (X) at exact cor. point and mark CC on S. with 2 grooves on S. and 3 grooves on E. face, from which
A Pine 10" dia., bears S.4°E., 113 lks. dist. mkd. T31S R2W S27 BT.
A Cedar 10" dia., bears S.62°W., 38 lks. dist. mkd. T31S R2W S28 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-73

Found - 12"x24"x16" stone, "CC" on S. face, out of ground.
10" now 14" Pine, S.4°E., 74.6 ft., opened for scribe "31S2 "27"
10" Cedar S.62°W., 25.1 ft., opened old scar to blaze, no scribe.

Along East side of corner stone, Set brass cap mkd.

County Surveyors Office

T 31 S R 2 W

S 22

S 28 | S 27

1966

New BTs- 14" Cedar S.21°E., 26.1 ft. mkd. T31S R2W S27 CS BT.

12" D.Fir S.29°W., 19.1 ft. mkd. T31S R2W S28 CS BT.