

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7633)

-----  
Set an ironstone 12x8x6 ins., 8" in the ground for 1/4 sec. cor. marked 1/4 on N. face, from which  
A Fir 15" dia., bears N.31°W., 18 lks. dist. mkd. 1/4 S27 BT  
A Fir 18" dia., bears South 25 lks. dist., mkd. 1/4 S34 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July - C.S. File 54/28-23

-----  
Found - Ironstone at 1/4 corner with "1/4" on North face.  
15" Fir, now dead, N.31°W., 11.9 ft., opened for scribe.  
18" Fir, now dead, South 16.5 ft., shows good scar.  
Set Brass cap alongside stone mkd: County Surveyors Office  
T 31 S R 2 W  
1/4 S 27  
S 34

New BTs- 15" D.Fir S.71°E., 34.3 ft. mkd. 1/4 S34 CS BT.  
19" D.Fir N.76°W., 3.0 ft. mkd. 1/4 S27 CS BT.

Survey by Bruce A. Shaner - For: U.S. Forest Service - July 1980 - C.S. File 58/229-27

-----  
Found - 2 1/2" brass cap, properly mkd.  
Original corner stone set alongside cap mkd. "1/4".  
18" D.Fir stump, orig. BT, scribes visible, bears N.31°W., 11.9 ft.  
20" D.Fir stump, orig. BT, scribes visible, bears South 16.5 ft.  
15" D.Fir snag, scribes visible, bears S.71°E., 34.3 ft.  
19" D.Fir snag, scribes visible, bears S.69°W., 21.6 ft.  
New BT - 10" D.Fir scribed "1/4 S34 BT", bears S.69°W., 21.6 ft

Survey by Gerald Nygren - March 20, 1988 - C.S. File 63/69-21

-----  
Found - 2" Iron pipe with 1966 DCSO brass cap which an original stone sets alongside, mkd. 1/4.  
18" D.Fir stump bears N.31°W., 11.9 ft., visible scribe.  
20" D.Fir stump bears South, 16.5 ft., visible scribe.

(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

15" D.Fir snag bears S.71°E., 34.3 ft., visible scribe.  
19" D.Fir snag bears N.76°W., 3.0 ft., visible scribe.  
12" D.Fir bears S.69°W., 21.6 ft., visible scribe.  
New BT - 5" D.Fir bears N.18°E., 31.6 ft. scribed "X" in small upper blaze and "BT" in small lower blaze. A ½" brass washer is nailed flush in lower blaze.