

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 440340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Survey by Glenn S. Baughman - For: U.S. Forest Service - Jan. 1975 - C.S. File 58/32-00A and M 56-6

-----

Set 30" long, 2½" galv. I.P., 25" in the ground, with mound of rock, with a 3" brass cap stamped: "T31S R2W C ¼ S22 RLS 536 1975", from which

A Cedar 11", bears S.19°E., 16.2 ft. scribed C¼ S22 BT with brass washer stamped LS 536 nailed at BT blaze.

A W.Fir 7" bears S.78°W., 13.1 ft. with brass washer stamped LS 536 nailed at BT blaze.

Both trees have a 6" red band painted around trees. Corner lies in edge of Fir and Cedar thicket. Corner bears N.51°W., 196 ft. from NW. corner of partially collapsed building, and 3 ft. South of old blaze lines.