

PRIMARY CORNER DESCRIPTION Center 1/4 Corner for Sec. 15

Alias	Description

Survey by Glenn S. Baughman - For: U.S. Forest Service - Jan. 1975 - C.S. File 58/28 and M 56-2

-----  
(Witness Corner set for Center 1/4 Corner)

Set 30" long, 2½" dia., galv. Iron pipe, 24" in the ground, in a mound of stones, with a 4" brass cap mkd: "T31S R2W WC 238.50 ft. C ¼ S15 1974 RLS 536", fro which

A Pine 10" bears N.20°05'E., 133.1 ft. scribed WC C¼ S15 BT, brass washer stamped "RLS 536".

A Pine 7" bears S.02°05'W., 59.2 ft. scribed WC C¼ S15 BT, with brass washer stamped "RLS 536"/.

Bearing trees have a 6" band of red painted around tree. Corner is set on centerline of Sec. 15, N.89°51'44"E., 238.50 ft. from center ¼ S15 and lies in an open field 150 ft. West of road.

(Witness Corner set for Center 1/4 Corner)

Set 30" long, 2½" galv. I.P., 26" in the ground, in a mound of stones with 4" brass cap mkd: "T31S R2W WC 127.04 ft. C¼ S15 RLS 536 1974", from which

A Cedar 14" bears S.2°E., 147.0 ft. scribed WC C¼ S15 BT with brass washer stamped RLS 536.

A Fir 7" bears S.19°W., 151.2 ft. scribed WC C¼ S15 BT with brass washer stamped RLS 536.

Bearing trees have a 6" band of red painted around tree. Corner is set on centerline of section 15, S.0°18'12"W., of true C 1/4 and lies in open field approx. 150 ft. West of road and approx. 110 ft. North of timber line to South of corner.