TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7603)

Set ¼ sec. post, from which
An Oak 10" dia., bears N.31°E., 95 lks.
An Oak 8" dia., bears S.79°E., 60 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew -July 1966 - C.S. File 54/28-56

Found - 10" W.Oak now 17", N.31°E., 62.7 ft.,tree partly opened.
8" Oak stump, S.79°E., 39.6 ft., opened stump for scribing "BT".

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ S 10 / S 15
1966

New BTs- 18" D.Fir S.18°E., 26.6 ft. mkd. ¼ S15 CS BT.
23" D.Fir N.27°W., 8.4 ft. mkd. ¼ S10 CS BT.
Corner lies in N-S fence, fence corner is North 39.0 ft.

Fd. and used in BLM resurvey by Donevan C. Harris, Cadastral Surveyor, under Group #755, surveyed Aug. 1971 - (DCSO records Vol. 38 Page(s) 14534)

Survey by Bruce Shaner - For: U.S. Forest Service - Feb. 1981 RM 3-44

Found - 1966 DCSO brass cap, properly marked.
26" D.Fir BT, scribes visible, bears N.27°W., 8.4 ft
New BT - 10" D.Fir, I scribed "¼ S15 BT", bears S.64°W., 14.9 ft.