

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 444100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, T32-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 20 Page(s) 8326)

-----  
Intersect S. bdy. of T31S R2W, 160 lks. East of the ¼ sec. cor. on the S. bdy. of sec. 34.

At point of intersection, set an ironstone, 18x12x12 ins., 12" in ground for closing cor. of sec. 3 & 4, marked C.C. on the S. face, with 3 grooves on the E. and W. faces, from which

A Fir 24" dia., bears S.66°E., 38 lks. dist. mkd. T32S R2W S3 BT.

A Fir 12" dia., bears S.36°W., 29 lks. dist. mkd. T32S R2W S4 BT.

Fd. and used in GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7616)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & C.Stone, crew - Sept. 1966 - C.S. File 54/28-86

-----  
Found - 16x12x10 stone at corner with "CC" on S. face; 3 notches on E. face; 2 notches on W. face, firmly set in ground.

Orig. 24" now 31" D.Fir, S.66°E., 25.1 ft. (I find to be S.33°E.) Tree opened for scribe.

Orig. 12" D.Fir S.36°W., 19.1 ft. (I find to be S.60°W. 19.1 ft.) Tree opened for scribe "4BT".

Tree in good condition.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W

S 34

S 4 | S 3

T 32 S

1966