

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 18 Page(s) 7613)

Set an ironstone 24x8x8 ins., 18" in the ground for cor. of secs. 34 and 35 marked with 2 notches on E. and 4 notches on W. edges, from which
A Fir 20" dia., bears N.76½°E., 19 lks. dist. mkd. T31S R2W S35 BT.
A Fir 18" dia., bears N.20½°W., 56 lks. dist. mkd. T31S R2W S34 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7616; 7630; 7639)

(Page 7616)
The cor. of secs. 34 and 35 which is an ironstone 6x8x8 ins. above ground, firmly set and marked and witnessed as described by the surveyor general.
(Page 7630)
The old cor. of secs. 34 and 35
I destroy the cor. and marks on bearing trees.
(Page 7639-40)
Intersect S. bdy. of the township, 35.11 chs., N.89°55'E., of the closing cor. of secs. 3 & 4, T32S R2W.
Set a basalt stone 15x6x6 ins., 10" in the ground for closing cor. of secs. 34 and 35 marked CC on N. with 2 grooves on E. and 4 grooves on W. face, from which
A Fir 36" dia., bears N.10°E., 50 lks. dist. mkd. T31S R2W S35 BT.
A Fir 16" dia., bears N.48°W., 33 lks. dist. mkd. T31S R2W S34 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-50

Found - 15x6x6 basalt stone mkd. with notches & CC on North face.
36" D.Fir now stump, N.10°E., 33.0 ft. (Dist. should be 47.2 ft.), scribe visible "2 W".
16" D.Fir now 24", N.48°W., 21.8 ft. Had been opened but pitched over.
Set corner with 2 correct bearings and 1 distance which fall at corner stone.

(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set Brass cap at cor. mkd:

County Surveyors Office

T 31 S R 2 W

S 34 | S 35

S 3

T 32 S R 2 W

1966

New BT - 28" Cedar N.1½°W., 32.6 ft. mkd. T31S R2W S35 CSBT

A 12" Yew post at fence corner, N.31°W., 21.3 ft.