

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7632-33)

-----  
Set conglomerate stone 18x12x8 ins., 12" in the ground for cor. of secs. 26, 27, 34 and 35, marked with one notch on S. and 2 notches on E. edge, from which  
A Yellow Pine 12" dia., bears N.23°E., 106 lks. dist. mkd. T31S R2W S26 BT.  
A Fir 18" dia., bears S.79°E., 91 lks. dist. mkd. T31S R2W S35 BT.  
A Madrone 15" dia., bears S.38°W., 83 lks. dist. mkd. T31S R2W S34 BT.  
A Yellow Pine 40" dia., bears N.65°W., 16 lks. dist. mkd. T31S R2W S27 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-25

-----  
Found - Pieces of corner stone.  
Orig. 12" Pine, now snag, N.23°E., 70.0 ft. (Brg. should be N.13°E.), scribe visible "1S 26 T"  
Orig. 18" Fir, now stump, S.79°E., 60.1 ft., opened for scribe "2".  
Orig. 15" Laurel now 20", S.38°W., 54.8 ft., rotten face.  
Orig. 40" now 44" Pine N.65°W., 10.6 ft., scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 2 W  
S 28 | S 26  
S 34 | S 35  
1966

New BTs- 9" Laurel S.29½°E., 7.2 ft. mkd. T31S R2W S35 CS BT  
10" D.Fir S.31°W., 31.0 ft. mkd. T31S R2W S34 CS BT  
8" D.Fir N.86°E., 15.5 ft. mkd. T31S R2W S26 CS BT.