

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7640)

-----  
Set a basalt stone 15x8x6 ins., 10" in the ground for ¼ sec. cor. marked ¼ on W. face, from which  
A Fir 20" dia., bears S.23°E., 6 lks. dist. mkd. ¼ S26 BT  
A Fir 24" dia., bears N.67°W., 7 lks. dist. mkd. ¼ S27 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-21

-----  
Found - No stone at corner.  
Orig. 20" Fir now 21", S.23°E., 4.0 ft. Tree had been opened for scribe.  
Orig. 24" now 25" Fir, N.67°W., 4.6 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 2 W  
S 27 | S 26  
1966

Reblazed and rescribed:  
21" D.Fir S.23°E., 4.0 ft. scribed "¼ S27 CS BT"