

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22 & 23 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7597)

Set post cor. secs. 22, 23, 26 and 27, from which
A Fir 12" dia., bears N.27°E., 15 lks.
A Fir 12" dia., bears S.40°W., 12 lks.
A Fir 12" dia., bears S.50°E., 30 lks.
A Pine 30" dia., bears N.62°W., 22 lks.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7641)

The old cor. of secs. 22, 23, 26 and 27 is nearly obliterated. No trace is found by the post and the NE. bearing tree is destroyed by fire, the other deeply overgrown. I reestablish the cor. in its original position as follows for cor. secs. 22 and 23 only.
Set a basalt stone 24x12x6 ins., 18" in the ground for cor. of secs. 22 and 23 marked with 2 notches on E. edge, from which
A Fir 14" dia., bears N.11°E., 71 lks. dist. mkd. T31S R2W S23 BT.
A Pine 36" dia., bears N.62°W., 22 lks. dist. mkd. T31S R2W S22 BT.
Old marks referring to secs. 26 and 27 already obliterated.

Survey by John H. Markham, Jr. - March 26, 1952 - C.S. File 41/1-4

List of orig. BTs as found:
12" Fir N.27°E., 15 lks. (not found)
12" Fir S.40°W., 12 lks. (dead snag, fallen)
12" Fir S.50°E., 30 lks. (dead snag, standing)
30" Pine N.62°W., 22 lks. (logged, scribe on stump)
20" Fir N.11°E, 71 lks. (good shape)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28

Found - 30" Pine stump, N.62°W., 14.5 ft., scribe visible.
20" Fir now 21", N.11°E., 46.9 ft., shows good scar.
Tree burned and looks unhealthy in general.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
S 22 | S 23

S 26
1966

(Cont. Next Page)

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22 & 23 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

This corner lies in fence corner.
New BTs- 9" Cedar N.46°E., 27.7 ft. mkd. T31S R2W S23 CS BT.
9" W.Fir West, 48.0 ft. mkd. T31S R2W S22 CS BT.

Fd. and used in BLM resurvey by Donevan C. Harris, Cadastral Surveyor, under Group #755, surveyed Aug. 1971 - (DCS0 records Vol. 38 Page(s) 14529-30)