

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7598)

Set post cor. secs. 14, 15, 22 and 23, from which
A Fir 15" dia., bears S.75°W., 6 lks.
A Fir 10" dia., bears N.10°W., 25 lks.
A Fir 18" dia., bears N.18°E., 23 lks.
A Fir 10" dia., bears S.89°E., 47 lks.

Survey by John H. Markham, Jr. - Wit: Elmer Sutton - Mar. 26, 1952 - C.S. File 41/1-2

Determined by O.B.T.s:
A Fir stump 23" dia., logged, bears S.75°W., 4.0 ft.
A W.Fir 26" dia., bears S.89°E., 32.4 ft.
A Fir stump 22" dia., logged, bears N.18°E., 15.7 ft.
At corner point, SET a 3/4" x 15" Iron pipe, from which
A Yew 8" dia., bears N.70°W., 40.5 ft. mkd. S15 BT.
A W.Fir 14" dia., bears S.77°W., 26.2 ft. mkd. S22 BT.
A W.Fir 12" dia., bears S.24°E., 33.0 ft. mkd. S23 BT.
A Cedar 8" dia., bears N.42°E., 40.0 ft. mkd. S14 BT.
Creek bears East, 150.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-60

Found - I.Pipe at sec. corner.
Orig. 15" Fir, now stump, S.75°W., 4.0 ft.
11" Cedar N.42°E., 40.0 ft. "S14" scribe visible.
No other trees found. Logged.

Set Brass cap at cor. mkd: County Surveyors Office

T	31	S	R	2	W
S	15	S	14		
S	22	S	23		

1966

New BTs- 12" Cedar N.2°W., 27.3 ft. mkd. T31S R2W S15 CS BT
15" Cedar S.31°W., 58.9 ft. mkd. T31S R2W S22 CS BT
Creek bears East, 150.0 ft.

Cor. Fd. and used in BLM resurvey by Donevan C. Harris, Cadastral Surveyor, under Group #755, surveyed Aug. 1971 - (DCSO records Vol. 38 Page(s) 14531)