

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7600)

-
- Set post cor. secs. 2, 3, 10 and 11, from which
- A Pine 9" dia., bears N.52°E., 102 lks.
 - A Pine 40" dia., bears S.60°E., 84 lks.
 - An Oak 18" dia., bears N.73°W., 61 lks.
 - An Oak 30" dia., bears S.62°W., 98 lks.

H. L. Eppstein, Co. Surveyor - Wit: N.E. Richardson; C.A. Bachman; Harry Dourney - Oct. 5, 1928 - Vol. 3 Page 287

-
- Set corner where California-Oregon Power Co. had driven stake, which tallied out with Oak tree on which I.S. Bannon said had seen scribe marks but were burnt out at this time. Pine SE. was in evidence and also Oak SW. Set for corner, 4" x 4" x 4 ft. Oak post and marked new witness trees:
- A 20" Fir N.15°W., 88 lks.
 - A 12" Fir S.79°E., 81 lks.
 - A 5" W.Oak N.38°E., 45 lks.
 - A 15" Fir S.31°W., 133 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-76

-
- Found - 20" Fir, now stump, N.15°W., 58.1 ft.
 12" Fir, now stump, S.79°E., 53.5 ft., opened stump "BT".
 15" now 21" Fir, S.31°W., 87.8 ft., shows good scar.
 5" now 10" Oak, N.38°E., 29.7 ft., scribe visible "2 CS".

Set Brass cap at cor. mkd: County Surveyors Office

T	31	S	R	2	W
	S	3		S	2
	S	10		S	11
					1966

- New BTs- 7" D.Fir S.45°E., 31.0 ft. mkd. T31S R2W S11 CS BT.
 16" Laurel N.52°W., 38.0 ft. mkd. T31S R2W S3 CS BT.
 16" D.Fir S.51°W., 17.8 ft. mkd. T31S R2W S10 CS BT

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hillman - 6/17/2015 - C.S. File 65/90-48

-
- Found - A 2½" brass cap on 1¼" galvanized iron pipe, projecting 8" above a mound of stone.
 No trace found of a (9" pine). Large pine in vicinity previously opened (N.52°E., 67.3 ft) 1857
 continued next page

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No trace found of a (40" pine) (S.60°E., 55.4 ft) 1857
Rotten remains of an indeterminate size oak with no marks visible. (N.73°W., 40.3 ft) 1857
No trace found of a (30" oak) (S62°W - 64.7 ft) 1857
A 34" fir stump with ax work visible. No visible face. (N.15°W., - 58.1 ft) 1928
An indeterminate size fir windfall log with no marks or root hole. (S.79°E., 53.5 ft) 1928
A 9" oak with a healed double blaze. (N.38°E., 29.7 ft) 1928
A 27" fir with a healed single blaze. (S.31°W., 87.8 ft) 1928
A 16" fir with a healed double blaze. (S.45°E., 31.0 ft) 1966
A 26" madrone with a faint healed single blaze. (N.52°W., 38.0 ft) 1966
A 26" fir with a healed double blaze. (S.51°W., 17.8 ft) 1966
No new accessories added. No new measurements taken.
Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.
Lat: N 42°54'07.296" Long: W 122°55'22.053"
Ellipsoid Height: 1735 ft.
Datum: WGS 84
Source: Cell phone GPS, for navigation to corner.