

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6753)

-----  
Set post cor. secs. 2, 3, 34 and 35, from which  
A Fir 24" dia., bears S.80°W., 25 lks.  
A Fir 18" dia., bears S.45°E., 25 lks.  
A Fir 24" dia., bears N.30°E., 18 lks.  
A Cedar 6" dia., bears N.36°W., 34 lks.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Sept. 22, 1966 - C.S. File 54/28-70

-----  
Found - No trace of SE. BT.  
24" now 32" D.Fir S.80°W., 16.5 ft., faint bark scribe and scar visible.  
24" now 28" D.Fir N.30°E., 11.9 ft., bark scribe visible.  
6" now 15" Cedar N.36°W., 22.4 ft., scribe visible "S3".

Set Brass cap at cor. mkd: County Surveyors Office 1966  
T 30 S R 2 W  
S 34 | S 35  
S 3 | S 2  
T 31 S

Reblazed and rescribed:  
32" D.Fir S.80°W., 16.5 ft. scribed "T31S R2W S3 CS BT".  
28" D.Fir N.30°E., 11.9 ft. scribed "T30S R2W S35 CS BT".  
New BT - 6" D.Fir S.38°E., 18.3 ft. scribed "S2 CS BT".  
This corner lies about 60.0 ft. South of small draw.

-----  
Jonathan B. Drew, II, USFS - Assisted by: Andrew Hellman & Jacob Hunt - 9/7/2016 - C.S. File 65/93-44

-----  
Found - A 1¼" galv iron pipe with a 2½" brass cap projecting 24" above the ground, loose and leaning heavily to the north. Reset monument vertical at the position determined by the base of the fd post, cap now projects 10" above the ground.  
A 37" fir bears, N.84°W., 16.6 ft, with a healed single blaze. (S.80°W., 16.5 ft) 1857  
No trace found of a (18" fir) 1857 (S.45°E., 16.5 ft) 1857.  
A 28" fir snag bears, N.35°E., 12.0 ft, with a healed single blaze, (N.30°E., 11.9 ft) 1857

continued next page

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T30-2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A 25" cedar bears, N.35°26'W., 22.3 ft, with a healed double blaze, (N.36°W., 22.4 ft) 1857  
A 14" fir bears, S.36°48'E., 17.9 ft, with a healed double blaze, (S.38°E., 18.3 ft) 1966  
New - A 12" Fir bears, N.52°E., 30.3 ft. mkd "T30SR2WS35" "BT" on a double blaze. New BT includes a 3/4" brass washer "ORPLS#89396" nailed between B & T.  
Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height.  
Lat: N.42°54'59.915" Long: W.122°55'21.427"  
Datum: WGS 84  
Source: USGS Quad map, for navigation to corner.