

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 18 Page(s) 7614)

Set a basalt stone 24x12x4 ins., 18" in the ground for ¼ sec. cor. mkd. ¼ on the N. face, from which
A Fir 24" dia., bears N.5°E., 38 lks. dist. mkd. ¼ S35 BT.
A Fir 18" dia., bears N.4½°W., 20 lks. dist. mkd. ¼ S35 BT

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7616)

(Page 7616)
The ¼ sec. cor. on S. bdy. sec. 35, which is a basalt stone 6x10x4 ins. above ground, firmly set and mkd. and witnessed as described by the surveyor general.

(Page 7630)
(40.04 chs.)
Point for ¼ sec. cor. falls on a basalt rock in place, 6x20x12 ins. above ground on which I cut a cross (X) at exact cor. point, ¼ on N. side, from which
A Fir 10" dia., bears N.10°E., 30 lks. dist. mkd. ¼ S35 BT
A Fir 12" dia., bears N.50°W., 48 lks. dist. mkd. ¼ S35 BT
(42.78 chs.)

The old ¼ sec. cor.
I destroy the cor. and marks on bearing trees.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-49

Found - 12" now 24" D.Fir, N.50°W., 31.7 ft., opened for scribe.

No trace of NE. BT nor stone, ground very steep.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W
¼ S 35
T32S
1966

New BT - 5" D.Fir N.15½°E., 27.8 ft. scribed ¼ S35 CS BT.

Fd. OK, July 1978 by G. Baughman - C.S. File 58/173