

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7632)

-----  
Set an iron stone 15x12x6 ins., 10" in the ground for ¼ sec. cor., marked ¼ on N. face, from which

A Cedar 60" dia., bears N.45°W., 19 lks. dist. mkd. ¼ S26 BT.

A Cedar 12" dia., bears S.32°E., 10 lks. dist. mkd. ¼ S35 BT.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-27

-----  
Found - Iron stone at ¼ corner.

Orig. 60" Cedar now stump, N.45°W., 12.5 ft., opened stump for scribing.

Orig. 12" Cedar, now dead, S.32°E., 6.6 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W

¼  $\frac{S \ 26}{S \ 35}$

1966

New BTs- 15" D.Fir S.38½°E., 32.1 ft. mkd. ¼ S35 CS BT.

15" Cedar N.6°E., 47.3 ft. mkd. ¼ S26 CS BT.