

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7600)

A Pine, 8" dia., ¼ sec. post, from which
A Pine 10" dia., bears N.60°W., 10 lks.
A Fir 18" dia., bears S.80°W., 14 lks.

H.L. Eppstein, Co. Surveyor - Wit: N.E. Richardson; C.A. Bachman; Harry Dourney - Oct. 5, 1928 - Vol. 3 Page 287

Found Pine tree as corner and the witness tree NW.
Set post and marked new BTs:
A 24" Fir N.71°W., 24 lks.
A 10" Fir S.36°E., 44 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - Aug. 1966 - C.S. File 54/28-77

Found - 24" now 31" Fir, N.71°W., 15.8 ft., opened for scribing "1 S".
10" Fir, now stump, S.36°E., 29.0 ft., no scribing found.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ S 2
S 11
1966

New BT - 9" D.Fir S.27°W., 25.4 ft. mkd. ¼ S11 CS BT.
This corner lies 2.0 ft. North of E-W fence line and 12.0 ft. E. of fence corner.

Survey by Glenn Baughman - For: U.S. Forest Service - March 1978 - M 65-68

Found - 1966 County brass cap.
24" D.Fir, now 34", bears N.71°W., 15.8 ft.
10" D.Fir stump, bears S.36°E., 29.0 ft.
9" D.Fir bears S.27°W., 25.4 ft., down.
New BT - 8" D.Fir bears S.34°E., 23.0 ft. scribed ¼ S11 BT.

Roberta D. Romeo, USDA Forest Service - Wit: Lance Goucher & Andrew Hellman - March 17, 2008 - C.S. File 65/63-31

Found - Co. Surveyor monument with brass cap (properly mkd), set in 1966
A fir snag, 38" dia., bears N.69°45'W., 16.3 ft.,
A fir, 20" dia., bears S.30°30'E., 22.6 ft. with
healed blaze. continued next page

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A rotten fir stump, bears S.36°45'E., 29.2 ft.
New BT - A pine, 15" dia., bears N.49°W., 54.6 ft. mkd: "¼ S2
BT"
Note - Corner lies on broad ridge, in fence line +/- ft.
200 south of cattle guard on FS road 1610-050.

Fd. ok by Dave Beedle, 7/2008 - M156-46

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hillman -
7/7/2015 - C.S. File 65/90-49

Found - A 2½" brass cap on a 1¼" galvanized iron pipe,
projecting 14" above the ground.
No trace fd of a (10" pine) (N.60°W., 6.6 ft.) 1857
No trace fd of a (18" fir) (S.80°W., 9.2 ft.) 1857
A 38" fir snag with previously opened upper blaze &
healed lower blaze (N.71°W., 15.8') 1928;
(N.69°45'W., 16.3') 2008
An indeterminate size fir stump with no marks visible.
(S.36°E., 29.0') 1928 (S.36°45'E., 29.2') 2008
A 15" fir stump shell with a healed single blaze.
(S.27°W., 25.4 ft.) 1966
A 20" fir with a healed double blaze. (S.34°E., 23.0')
1978 (S.30°30'E., 22.6') 2008
A 17" pine with a healed double blaze. (N.49°W., 54.6
ft.) 2008
No new accessories added. No new measurements taken.
Clear brush from around monument and to BTs. Tie
flagging to monument and guard posts, paint BT
faces & a 6" band at head height, add new nails
to existing BT tags & add new tags where needed.
Lat: N 42°54'06.73338" Long: W 122°54'45.99064"
Ellipsoid Height: 1804.5 ft.
Datum: NAD 83 (2011) (EPOCH: 2010.0000)
Source: Direct occupation, RTK & static GPS, OPUS
corrected base.