

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 544100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, T32-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 20 Page(s) 8315)

Intersect S. bdy. of T31S R2W, 150 lks. East of the ¼ sec. cor. on the S. bdy. of sec. 35. At point of intersection, Set a basalt stone 28x12x6 ins., 21 ins. in ground, for closing corners of secs. 2 and 3, marked C.C. on S. face, with 2 grooves on E. and 4 grooves on W. faces, from which
A Fir 18" dia., bears S.29½°E., 56 lks. dist. mkd. T32S R2W S2 BT.
A Fir 30" dia., bears S.19°W., 94 lks. dist. mkd. T32S R2W S35 BT.

Fd. and used in GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7616)

Looked for, not found. No record found for this info. Symbol on former visual counter page. Probably by DCSO in the 1960's.