

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7638)

Set an ironstone 12x10x6 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 18" dia., bears N.73°E., 42 lks. dist. mkd. ¼ S36 BT
A Fir 18" dia., bears S.40°W., 42 lks. dist. mkd. ¼ S35 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-33

Found - No trace of stone.
18" D.Fir now 24", N.73°E., 27.7 ft., opened tree for scribe.
18" D.Fir now 24", S.40°W., 27.7 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ S 35 | S 36
1966

Reblazed and rescribed:
24" D.Fir N.73°E., 27.7 ft. mkd. ¼ S36 CS BT.
Bluff bears N.40°W. about 80.0 ft.

Fd. OK, July 1978 by G. Baughman - C.S. File 58/173-4