

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7594)

-----  
Set ¼ sec. post, from which  
A Fir 24" dia., bears N.14°E., 45 lks.  
A Fir 14" dia., bears N.15°W., 30 lks.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-32

-----  
Found - 24" Fir now snag, N.14°E., 29.7 ft. scribe visible "¼S BT". (Find this to be N.33°E., 19.8 ft.)  
14" now 32" Fir N.15°W., 19.8 ft. (Find this to be 29.7 ft.) I opened this tree for "BT" and by ring count place it at about 1857. (Orig. survey)

Direction of faces are very good for reversing distances.

Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 2 W  
¼ S 23 | S 24  
1966

Set ¼ corner by using 2 original distances reversed and 1 original bearing.

New BTs- 13" Laurel N.22°E., 14.2 ft. mkd. ¼ S24 CS BT.  
7" Laurel N.49°W., 17.3 ft. mkd. ¼ S23 CS BT.