

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7594)

-----  
Set post cor. secs. 13, 14, 23 and 24, from which  
A Laurel 12" dia., bears N.26°W., 140 lks.  
A Cedar 12" dia., bears S.87°E., 415 lks.  
A Fir 18" dia., bears S.1°W., 394 lks.  
A Fir 12" dia., bears S.83°W., 227 lks.  
A Fir 18" dia., bears N.73°E., 230 lks.

-----  
Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-61

-----  
Found - 18" D.Fir now snag 30", S.1°W., 260.0 ft., opened for scribing "2". (Found dist. to be 265.0 ft.)  
12" D.Fir now 30", S.83°W., 149.8 ft., shows good scar. (Found dist. to be 143.7 ft.)

No trace of NW.; SE.; nor NE. BTs.

Set Brass cap at cor. mkd: County Surveyors Office

T 31 S R 2 W  
S 14 | S 13  
S 23 | S 24  
1966

New BTs- 27" Cedar S.3½°E., 252.3 ft. mkd. T31S R2W S24 CS BT  
9" Laurel N.24°W., 87.5 ft. mkd. T31S R2W S14 CS BT.

This corner lies on open South slope.