

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7595)

Set ¼ sec. post, from which
 An Oak 12" dia., bears N.10°W., 30 lks.
 An Oak 10" dia., bears S.35°E., 39 lks.

Ben B. Irving, Deputy County Surveyor - Wit: N.E. Richardson;
B.A. Lane; F.L. Thomas - Jan. 1931 - M 1-38

Position identified from one orig. BT, badly rotted scribe barks still visible. Position of other orig. BT, identified by rotted stump.
Set sandstone 6" x 12" x 14" long, 12" in ground for cor., chise+++led ¼ on top, from which
 Fir 14" dia., N.49°E., 14 lks. mkd. ¼ S13 CS BT.
 Fir 26" dia., N.62°W., 25 lks. mkd. ¼ S14 CS BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-13

Found - Unrecorded 1½" I.P. at corner.
 No trace of stone.
 14" Fir, N.49°E., 9.2 ft. - No trace of this BT.
 26" Fir, now stump, N.62°W., 16.6 ft., opened for scribing. (This stump is out of place but renewed by using stump hole.)
Set Brass cap at cor. mkd: County Surveyors Office
 T 31 S R 2 W
 ¼ S 14 | S 13
 1966
New BTs- 11" W.Oak S.77°E., 125.0 ft. scribed ¼ S13 CS BT
 12" Cedar N.42°W., 218.7 ft. scribed ¼ S14 CS BT

FD. Ok by N. Hibbs, 8/2012 - M164-12A