

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7595)

Set post cor. secs. 11, 12, 13 and 14, from which
A Pine 24" dia., bears S.24°W., 72 lks.
A Pine 24" dia., bears N.25°W., 62 lks.
An Oak 15" dia., bears S.75°E., 7 lks.
A Fir 24" dia., bears N.45°E., 44 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit: N.E. Richardson; B.A. Lane; F.L. Thomas - Jan. 1931 - M 1-38 (and "old" cor. book, Page 159)

Renewed from three original BTs in good condition.
Conglomerate rock 6x8x16", 8" in ground.
A 24" Pine S.24°W., 72 lks.
A 15" Oak, now 20", S.75°E., 7 lks. - remarked.
A 24" Fir, now 30", N.45°E., 44 lks. - remarked.
New BT - 8" Fir N.37°50'W., 33 lks. scribed T31S R2W CS BT S11.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-15

Found - Stone at sec. cor. and 1/2" Iron pipe.
8" Fir N.37°50'W., 21.8 - No trace of this tree.
Orig. 24" Pine now 28", S.24°W., 47.5 ft., shows good scar.
Orig. 20" Oak now dead, S.75°E., 4.6 ft., faint scribe marks visible.
Orig. 30" now 45" Fir, N.45°E., 29.0 ft., bark scribed.

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
S 11 | S 12
S 14 | S 13
1966

New BTs- 9" D.Fir S.5°E., 22.5 ft. mkd. T31S R2W S13 CS BT
12" D.Fir N.28°W., 8.0 ft. mkd. T31S R2W S11 CSBT
Corner is 1.0 ft. North of fence corner, running E-W & S.

Fd. OK, May 1991 by J. Artman - M 113-61
FD. Ok by N. Hibbs, 8/2012 - M164-12A