

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7596)

Set ¼ sec. post, from which
 An Oak 15" dia., bears N.82°W., 70 lks.
 An Oak 12" dia., bears N.15°E., 98 lks.

H. L. Eppstein, County Surveyor - Wit: N.E. Richardson; G.A. Bachman; Harry Dourney - Oct. 5, 1926 - Vol. 3 Pg. 287

Set stone with ¼ S. Old bearing trees still standing but scribe marks rotted out.
Marked new BT:
 15" Fir S.64°W., 82 lks.
 8" Fir S.38°E., 53 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-36

Found - 15" Fir now 26", S.64°W., 54.1 ft., bark scribed "¼S BT".
 8" Fir now 17", S.38°E., 35.0 ft. shows good scar
 No trace of stone at ¼ corner.
Set Brass cap at cor. mkd: County Surveyors Office
 T 31 S R 2 W
 ¼ S 11 | S 12
 1966

Reblazed and rescribed:
 26" D.Fir S.64°W., ~~59.1~~ 54.1* ft. mkd. "¼ S11 CS BT"
This corner is in fence corner, fences running N.; S.; & W.
* Corrected 9/26/2018 JC DCSO