

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7596)

Set post cor. secs. 1, 2, 11 and 12, from which
An Oak 18" dia., bears S.13°W., 70 lks.
An Oak 18" dia., bears N.64°W., 28 lks.
An Oak 15" dia., bears N.72°E., 41 lks.
An Oak 18" dia., bears S.54°E., 60 lks.

Survey by John H. Markham, Jr. - 10/11/1960 (date added 8/5/2015) - C.S. File 42/392-70

Determined by O.B.T.s:
20" W.Oak bears N.72°E., 27.0 ft., found scribe.
15" W.Oak bears N.64°W., 21.0 ft., uproot.
At corner point, found stone and SET 1¼" x 36" truck axle with flange up, from which
10" Fir N.80°E., 25.6 ft. mkd. S1 R2W BT.
14" Cedar S.55°E., 20.5 ft. mkd. S12 X BT.
15" Cedar S.55°W., 36.6 ft. mkd. S11 R2W BT.
8" Fir N.34°W., 27.2 ft. mkd. S2 R2W BT.
Road bears South, 40.0 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-14

Found - Truck axle with flange at corner.
10" Fir N.80°E., 25.6 ft., pitched over scribing.
14" Cedar S.55°E., 20.5 ft. scribe visible "S12"
15" Cedar S.55°W., 36.6 ft., scribe visible "S2 R2W"
8" D.Fir, now dead, N.34°W., 27.2 ft.
New BT - 9" D.Fir N.67°W., 13.6 ft. mkd. T31S R2W S2 CS BT.
Road bears South, 40.0 ft.

Dennis Gaylord, U.S. Forest Service - (Deputized by the County) - Wit: Leonard Herzstein - April 16, 1980 - C.S. 61/6-30

Found - Truck axle set firmly in ground in a mound of stones. One stone in the mound of stones could be the orig. corner stone but no marks are visible on the stone.
Orig. BT is now a 18" Oak, bears N.70°E., 26.7 ft., scribing visible "BT" on a previously opened blaze.
A 12" D.Fir bears N.80°E., 25.6 ft. and has double healed blazes.
A 17" Cedar bears S.54°30'E., 19.9 ft. to center of tree at base. Scribing is visible on a nearly healed upper blaze, lower blaze is healed over. cont.

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec Cor for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 16" Cedar bears S.56°W., 36.8 ft. scribing visible on double blazes.
A 9" D.Fir bears N.66°W., 13.0 ft. has double healed blazes.
Moving the axle aside, I SET in its place a 1" x 30" Iron pipe with a 2½" brass cap mkd:" County Surveyors Office T31S R2W S1 S2 S11 S12 1980". I bury the axle horizontally alongside the iron pipe and build a rock mound around the pipe.
No new accessories established.
Corner is 40 ft. North of F.S. Road #301.

Fd. BC by Dave Beedle, 7/2008 - M156-46

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hillman - 7/2/2015 - C.S. File 65/90-50

Found - A 2½" brass cap on 1¼" galvanized iron pipe projecting 2" above a mound of stone.
No trace fd of a (18" Oak) (S.13°W., 46.2 ft.) 1857
No trace fd of a (18" Oak) (N.64°W., 18.5 ft.) 1857
A 19" oak snag bears N.68°30'E., 26.6 ft. with scribe visible on a partially healed double blaze. (N.72°E., 27.1 ft.) 1857
No trace fd of a (18" Oak) (S.54°E., 39.6 ft.) 1857
A 14" fir stump bears N.79°E., 25.6 ft. with a healed single blaze. (N.80°E., 25.6 ft.) 1960
No trace fd of a (14" cedar) (S.55°E., 20.5 ft) 1960
A 19" cedar bears S.54°30'W., 36.9 ft. with scribe visible on partially healed single blaze. (S.55°W., 36.6 ft.) 1960
No trace fd of a (8" fir) (N.34°W., 27.2 ft.) 1960
A 15" fir bears N.68°30'W., 12.9 ft. with a healed double blaze. (N.67°W., 13.6 ft.) 1966

New - A ⅝" rebar bears S.41°00'E., 7.63 ft. with a 2" alum. cap marked "RM PLS 89396 2015" and center punch.
A 14" cedar bears N.82°45'E., 26.0 ft. mkd "T31SR2WS1""BT" on a double blaze.

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.
Lat: N 42°54'06.396" Long: W 122°54'10.047"
Ellipsoid Height: 1905 ft.
Datum: WGS84
Source: Cell phone GPS, for navigation to corner.