

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7597)

-----  
Set ¼ sec. post, from which  
    An Oak 12" dia., bears S.75°W., 68 lks.  
    An Oak 18" dia., bears S.68°E., 87 lks.

Survey by Glenn Baughman - For: U.S. Forest Service - March 1978 - M 65-68

-----  
Set 2" x 30" I.P. with brass cap stamped "T31S R2W WM ¼ S2 S1 1978 OLS 536", from which  
    6" D.Fir bears S.33°W., 47.0 ft. scribed ¼ S2 BT.  
    9" D.Fir bears S.32°E., 35.4 ft. scribed ¼ S1 BT.

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hillman - 7/2/2015 - C.S. File 65/90-41

-----  
Found - 2½" brass cap on 2¼" galvanized iron pipe, projecting 7" above a mound of stone.  
    No trace fd of a (12" oak) (S.75°W., 44.9 ft) 1857  
    No trace fd of a (18" oak) (S.68°E., 57.4 ft) 1857  
    A 10" fir with a healed double blaze. (S.33°W., 47.0 ft) 1978  
    A 18" fir with a healed double blaze. (S.32°E., 35.4 ft) 1978  
    No new accessories added. No new measurements taken.  
    Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.  
    Lat: N 42°54'33.284" Long: W 122°54'09.859"  
    Ellipsoid Height: 2175 ft.  
    Datum: WGS 84  
    Source: USGS QUAD map for navigation to corner.