

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747,, dated May 5,1902 - (DCSO records Vol. 18 Page(s) 7615)

Set an ironstone 24x8x10 ins., 18" in the ground for ¼ sec. cor. mkd. ¼ on the N. face, from which
A Fir 24" dia., bears N.24½°E., 36 lks. dist. mkd. ¼ S36 BT.
A Fir 30" dia., bears N.21°W., 73 lks. dist. mkd. ¼ S36 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7615 and page 7631)

(Page 7615)
The ¼ sec. cor. on S. bdy. sec. 36, which is an ironstone 6x8x10 ins. above ground firmly set and mkd. and witnessed as described by the surveyor general.
(Page 7631)
(40.81½ chains)
Set a basalt stone 15x8x6 ins., 10" in the ground for ¼ sec. cor., marked ¼ on N. face, from which
A Fir 16" dia., bears N.55°E., 54 lks. dist. mkd. ¼ S36 BT
A Fir 14" dia., bears N.75°W., 25 lks. dist. mkd. ¼ S36 BT
(42.15 chs.)
The old ¼ sec. cor.
I destroy the cor. and marks on bearing trees.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - July 1966 - C.S. File 54/28-47

Found - 16" Fir stump, N.55°E., 35.6 ft., faint scribe visible. (I find this bearing to be N.50°E.)
14" D.Fir now 24", N.75°W., 16.5 ft., shows good scar.
No trace of corner stone.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
¼ S 36 T32S
1966
New BT - 4" D.Fir N.27½°E., 14.9 ft. mkd. ¼ S36 CS BT.

Fd. OK, July 1978 by G. Baughman - C.S. File 58/173-6