

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7593)

Set 1/4 sec. post, from which
A Laurel 6" dia., bears S.25°W., 12 lks.
A Laurel 15" dia., bears N.55°E., 12 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7669)

The 1/4 sec. cor. nearly obliterated.
The only remaining evidence is one bearing tree. I reestablish the cor. in its original position as follows:
Set a basalt stone 15x8x7 ins., 10" in the ground for 1/4 sec.cor. marked 1/4 on N. face, from which
A Madrone 20" dia., bears N.55°E., 12 lks. dist. mkd. 1/4 S25 BT.
A Madrone 8" dia., bears S.23°E., 22 lks. dist. mkd. 1/4 S36 BT.

Survey by Wm. Barnes - For: Umpqua National Forest - Oct. 1972 - M 42-77

Set 2" I.P. with 3" brass cap stamped as shown:
T31S R2W
1/4 $\frac{S \ 25}{S \ 36}$
1972 PE 2128

from which bears
A 12" D.Fir N.89°E., 5.5 ft. scribed 1/4 S25 BT PE2128.
An 18" D.Fir S.82°W., 13.8 ft. scribed 1/4 S36 BT PE2128.