

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7594)

-----  
Set ¼ sec. post, from which  
A Laurel 12" dia., bears N.65°E., 28 lks.  
A Laurel 15" dia., bears S.50°W., 28 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-24

-----  
Found - Orig. 12" Laurel, N.65°E., 18.5 ft., opened for scribing "BT".  
No trace of 15" Laurel S.50°W., 18.5 ft.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 31 S R 2 W  
¼ S 24  
S 25  
1966  
New BTs- 14" D.Fir N.38°W., 21.0 ft. scribed ¼ S24 CS BT.  
15" D.Fir S.58°E., 37.3 ft. scribed ¼ S25 CS BT.

Leonard Herzstein, U.S. Forest Service (Deputized by the County) - Wit: Jim Landrum & Tom Wolford - May 20, 1981 - C.S. File 61/24-29

-----  
Found - 1" I.P. set by Powell in 1966, firmly set, projecting 4" above ground, with brass cap properly mkd.  
Orig. BT, a 17" Madrone snag N.65°E., 18.5 ft. with scribe marks "BT" visible on previously opened blaze.  
1966 BT, a 17" D.Fir S.58°E., 37.3 ft. with healed double blaze.  
1966 BT, a 14" D.Fir snag, N.38°W., 21.0 ft. with scribe mark "¼ S24 CS BT" visible on partly healed blaze.  
New BT - 9" I.Cedar N.61°W., 70.3 ft. scribed "¼ S24 CS BT" on a double blaze.  
Brass cap is just outside fence corner, fence bears S. & W.