

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7595)

Set ¼ sec. post, from which
A Fir 24" dia., bears S.70°E., 20 lks.
A Fir 20" dia., bears N.40°W., 40 lks.

Ben B. Irving, Deputy County Surveyor - Wit: N.E. Richardson;
B.A. Lane; F.L. Thomas - Jan. 1931 - M 1-38

Position identified by mound of rock and both original BTs.
Set a sandstone chisled ¼ for corner and surrounded with mound of rock. Remarked Orig. BTs.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-30

Found - No trace of corner stone as recorded.
Orig. 24" Fir, now snag, S.70°E., 13.2 ft., rotten, nothing visible.
Orig. 20" now 34" Fir, N.40°W., 26.4 ft., bark scribe visible.

Set Brass cap in mound of stone 5' x 2.5' and mkd:

County Surveyors Office

T 31 S R 2 W

¼ S 13

S 24

1966

New BT - 20" D.Fir S.75½°W., 32.9 ft. mkd. ¼ S24 CS BT.

Reblazed and rescribed:

34" D.Fir N.40°W., 26.4 ft. mkd. ¼ S13 CS BT.