

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 640440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ben B. Irving, Deputy Co. Surveyor - Jan. 1931 - C.S. File 37/27 and M 1-38

Established by subd. of section.
Set truck axle, from which
 14" Fir N.2°E., 10 lks.
 16" Fir S.2°E., 20 lks.

Dennis Gaylord, U.S. Forest Service (Deputized by the County)
Wit: Roland Simshauser - Nov. 10, 1977 - C.S. File 59/42-10

Found - 1½" steel auto axle solidly set with top flush to ground. Corner is in a 3-way fence corner.
 A 20" orig. 16" D.Fir stump, bears S.7°E., 13.2 ft. Has a double healed blazes. (Rec. S.2°E.)
 A 22" orig. 14" D.Fir bears N.7°E., 7.5 ft. (Rec. N.2°E.) to center of tree. (Rec. dist. of 6.6 ft. is to face) Has a single blaze.
Set 2½" brass cap on a 1½" galv. iron pipe. Referencing the axle, I remove the axle and place the brass cap in the exact same location. I bury the axle alongside the brass cap. Cap stamped: "County Surveyors Office T31S R2W C ¼ . S13 1977".
New BT - 13" D.Fir bears N68°W., 56.7 ft. scribed "C ¼ S13 CS BT" on a double blaze.
Placed County BT signs on the orig. BT and the new BT.
Some local attraction may be caused by fence wires.

Fd. OK, May 1991 by J. Artman - M 113-61