

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7596)

Set 1/4 sec. post, from which
A Fir 12" dia., bears N.48°E., 48 lks.
A Fir 12" dia., bears S.36°E., 83 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy - Wit: N.E. Richardson; B.A. Lane; F.L. Thomas - Jan. 1931 - M 1-38

Position identified by one original BT in good shape which was chopped out. Scribe marks legible and well preserved, S.38°E., 83 lks.
Set sandstone 8"x8"x16", 14" in ground for corner mkd. 1/4, from which
A 12" Fir S.2°40'W., 43 lks. "1/4 S13 CS BT".
A 14" Fir N.21°20'E., 50 lks. "1/4 S12 CS BT".

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Terry Connell, crew - June/July 1966 - C.S. File 54/28-16

Found - Sandstone at 1/4 corner, faint "4".
12" Fir now 18", S.2°40'W., 28.4 ft., opened for scribe "B".
14" Fir now 21", N.21°20'E., 33.0 ft., shows good scar.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 2 W
1/4 S 12
S 13
1966
New BT - 9" Laurel S.51°W., 26.2 ft. mkd. 1/4 S13 CS BT.

Fd. OK, May 1991 by J. Artman - M 113-61