

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31, T31-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7459)

Set ¼ sec. post, from which
A Cedar 12" dia., bears N.10°E., 15 lks. dist.
A Cedar 15" dia., bears S.47°W., 22 lks. dist.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #766, dated May 10, 1906 - (DCSO records Vol. 18 Page(s) 7501-02)

The ¼ sec. cor. which is nearly obliterated, the only remaining evidence being one bearing tree, deeply overgrown. I re-establish the cor. in its original position as follows:
Set an ironstone, 14x10x4 ins., 9½" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Cedar 18" dia., bears N.10°E., 15 lks. dist. mkd. ¼ S31 BT.
A Cedar 28" dia., bears S.47°W., 22 lks. dist. mkd. ¼ S36 BT.

Fd. and used in GLO resurvey by Fred Mensch, U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 (DCSO records Vol. 18 Page(s) 7583)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Terry Connell, crew - July 1966 - C.S. File 54/28-45

Found - Stone at ¼ corner, marked "¼".
18" Cedar, down and rotten, N.10°E., 9.9 ft., found scribing "BT".
28" Cedar, now burned stump, S.47°W., 14.5 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 31 S
R ¼ S36 | S31 R
2W 1966 1W
New BTs- 6" D.Fir N.15°E., 17.9 ft. mkd. ¼ S31 CS BT.
8" D.Fir S.60°W., 17.0 ft. mkd. ¼ S36 CS BT.
This corner lies 50 ft. North of trail. Location tag on trail.

Fd. OK, July 1978 by G. Baughman - C.S. File 58/173-8