TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; and 30, T31-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7458-59)

Set ¼ sec. post, from which
A Laurel 12" dia., bears N.70°E., 28 lks. dist.
An Oak 15" dia., bears N.57°W., 39 lks. dist.

GLO resurvey by Fred Mensch , U.S. Cadastral Engineer - under special Instructions, dated June 7, 1922 (DCSO records Vol. 18 Page(s) 7584)

I locate corner by measurement from the bearing trees.
Set an Iron post 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked:

¼
S25|S30
1923

from which
A Laurel 18" dia., bears N.65°E., 28 lks. dist. mkd. ¼ S30 BT (Old BT)
A Fir 26" dia., bears N.51°W., 39 lks. dist. mkd. ¼ S25 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell; Frank Jones; Terry Connell, crew - July 1966 - C.S. File 54/28-44

Found - 12" now 20" Laurel N.70°E., 18.5 ft., opened for "BT" scribe.
15" Oak, N.57°W., 25.7 ft., no trace of this BT.
Reset 1922 GLO brass cap from 20" Laurel.
Reblazed and rescribed:
20" Laurel N.70°E., 18.5 ft. mkd. ¼ S30 CS BT.
New BT - 24" D.Fir S.81°W., 20.0 ft. mkd. ¼ S25 CS BT.