

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18, T31-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 18 Page(s) 7457-58)

-----  
Set ¼ sec. post, from which  
A Pine 36" dia., bears N.15°W., 31 lks. dist.  
A Pine 30" dia., bears S.74°E., 49 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson; B.A. Lane; F.L. Thomas - Jan. 1931 - M 1-38

-----  
Position identified by proportionate distances between section corners. Checked with holes where probable orig. BTs stood. Fire had burned all traces of original corner. Set a sandstone 8"x18"x18" long, 14" in ground, marked ¼, from which  
A 10" Fir N.32°E., 91 lks. mkd. ¼ S18 CS BT.  
A 14" Fir N.32°W., 74 lks. mkd. ¼ S13 CS BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Terry Connell, crew - July 1966 - C.S. File 54/28-42

-----  
Found - Sandstone at ¼ corner, no marks visible.  
10" Fir now 17", N.32°E., 60.1 ft., bark scribed "¼S" "B".  
14" Fir now 23", N.32°W., 48.8 ft. bark scribed "¼ S13 CS BT".

Set Brass cap at cor. mkd: County Surveyors Office  
R T 31 S R  
¼ 2W S 13|S 18 1W  
1966

Reblazed and rescribed:  
17" D.Fir N.32°E., 60.1 ft. mkd. ¼ S18 CS BT.  
23" D.Fir N.32°W., 48.8 ft. mkd. ¼ S13 CS BT.

This corner lies about 150 ft. South of high, rock bluffs that drop off to the West and North.