

PRIMARY CORNER DESCRIPTION S. 1/16 btwn. sec. 1; and 6 of T31-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Glenn Baughman - For: Tiller Ranger Dist. - June 20, 1967 - C.S. File 55/41 and M 34-23

Set 2½" bronze disk, set by single proportionate method, from which

6" Oak bears N.21°30'W., 32.3 ft. scribed S 1/16 S1 BT.
12" Oak bears S.12°W., 35.1 ft. scribed S 1/16 S1 CS BT.

Leonard Herzstein, U.S. Forest Service (Deputized by the County - Wit: Arciniega and Richey - Oct. 23, 1980 - C.S. File 61/11-33

Found - 2" dia. I.P. with 1967 brass cap, properly marked, facing East and leaning easterly, firmly set, projecting 20" above ground. Set by Baughman
W.Oak 10", bears S.9°44'W., 35.1 ft. (Rec. 32.3 ft.) with healed blaze.

W.Oak clump with 2 trunks, the easterly trunk 8" dia., bears N.24°14'W., 32.3 ft. (Rec. 35.3 ft.) with healed blaze.

Reset I.P. facing North, firmly set, projecting 8' above 2 ft. mound of stone.

BLM dependent resurvey by Leonard E. Herzstein, LS USFS, under Group No. 2013, surveyed May 2002/Feb. 2003 - (DCSO records Vol. 54 page(s) 20781-2

The S 1/16 sec. cor. of secs. 1 & 6 established by Baughman, in 1967, and perpetuated by Herzstein, in 1980 and accepted as the corner; monumented with an iron post, 2½" dia., firmly set, projecting 12" above ground and in a 2 ft dia. mound of stone, with brass cap (properly) mkd.

from which bearing trees mkd. by Baughman in 1967

A W.Oak, 11" dia., bears S.10½°W., 35.7 ft., with healed blaze.

A W.Oak, 8" dia., bears N.23½°W., 32.0 ft., with healed blaze.

At the corner point

Set a stainless steel post, 30" long, 2½" dia., 28" in the ground, in a collar of stone, with brass cap mkd.

S 1/16
S 1|S 6
2003

Deposit a magnet, in a white plastic case, at the base of the stainless steel post, and inverted and buried the old iron post alongside the new monument.

continued next page

TOWNSHIP 31 RANGE 02 POINT IDENTIFIER # 700620

PRIMARY CORNER DESCRIPTION S. 1/16 btwn. sec. 1; and 6 of T31-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hellman & Jacob Hunt - 8/15/2016 - C.S. File 65/93-51

Found - A 2½" stainless steel post with a 3" brass cap,
(properly mkd) projecting 1" above the ground.
A 9" oak with a healed single blaze, (N.21°30'W.,
32.3 ft) 1967 & (N.23°30'W., 32.0 ft) 2003
13" oak with a healed single blaze, (S.12°W., 35.1
ft) 1967, (S.10°30'W., 35.7 ft) 2003

No new accessories added.
Note - Clear brush from around monument and to BTs. Tie
flagging to monument and guard posts, paint BT
faces & a 6" band at head height.
Lat: N.42°54'20.004" Long: W.122°52'57.890"
Datum: WGS84