

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (Tsp. corner)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 18 Page(s) 7785)

-----  
Set post, cor. to Tps. 31 and 32 South, Rgs. 3 and 4 W., from which

- A Willow 5" dia., bears N.48°E., 14 lks. dist.
- A Willow 5" dia., bears S.48°E., 11 lks. dist.
- A Willow 5" dia., bears S.50°W., 9 lks. dist.
- A Willow 5" dia., bears N.45°W., 13 lks. dist.

George J. Wenderoth, Deputy Co. Surveyor - For: H.D. Hauck - May 1955 - C.S. File 46/134

- 
- 1¼" Iron pipe.
  - 8" Thorn, S.77°E., 48.8 ft.
  - 10" Hemlock S.33°40'W., 185.5 ft.
  - 24" Fir N.12°20'W., 142.0 ft.

Douglas Co. Surveyors Office - John M. Powell and crew - Jan. 13, 1966 - C.S. File 52/63-54

- 
- Found - Iron pipe at corner which was out of ground.
- 8" Thorn, now 18" S.77°E., 48.8 ft., scribe visible "S6CS BT"
  - 10" Hemlock now 12", S.33¼°W., 185.5 ft., scribe visible "BT"
  - 24" Fir stump, N.12°W., 142.0 ft.

Set Brass cap at twp. cor. mkd: County Surveyors Office

		T 31 S		
R	S	36	S 31	R
4	S	1	S 6	3
W		T 32 S		W
		1966		

- New BTs -6" D.Fir N.2°E., 120.3 ft. scribed S31 CS BT.
- 11" Hemlock S.75°E., 62.9 ft. scribed T32S R3W S6 CS BT.

The best way to reach corner is to wade Cow Creek in the summer.

Fd. OK, by R. Brown, April 1993, M 112-72  
FD. Ok by R. Brown, 2/2009 - M157-10

Ronald L. Rice, Ward NW - For: Seneca Jones Co. - Sept 2011 - C.S. File 65/74-17

-----  
Found - Douglas Co brass cap dated 1966 with the following accessories: continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31 (Tsp. corner)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

20" Hemlock stump bears S.33¼°W., 185.5' - scribing visible  
24" Fir stump bears N.12°W., 142.0' - rotted face  
28" D.Fir bears N.2°E 120.3' - healed face  
Other accessories of record not found  
New BT - 9" W.Fir bears S.86¼°E., 140.2' - scribed "T32S R3W S6 BT"