

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19; 13 & 24, T31-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7794)

Set a stone 24x14x12 ins., 18" in the ground for cor. to secs. 13, 18, 19 and 24, marked with 3 notches on N. and S. edges, from which

A Fir 14" dia., bears N.24°E., 5½ lks. dist. mkd. T31S R3W S18 BT.

A Fir 25" dia., bears S.58½°E., 66 lks. dist. mkd. T31S R3W S19 BT.

A Fir 18" dia., bears S.12¼°W., 42½ lks. dist. mkd. T31S R4W S24 BT.

A Fir 20" dia., bears N.46½°W., 23¼ lks. dist. mkd. T31S R4W S13 BT.

Survey by John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lumber Co. - April 28, 1959 - C.S. File 42/391-22

Determined by original BTs:

20" Fir bears N.24°E., 3.6 ft.

36" Fir bears S.58°E., 43.5 ft.

30" Fir S.12°W., 28.0 ft.

30" Fir N.46°W., 15.3 ft.

At corner point, SET 3/4" x 30" Iron pipe, from which

7" Fir bears S.7°W., 22.7 ft. mkd. S24 R4W BT.

16" Fir bears North 22.8 ft. mkd. S13 T31S R4W BT.

12" Fir bears N.62°E., 22.0 ft. mkd. S18 R3W BT.

Survey by Howard W. Johnstone, LS #498 - For: Roseburg Lumber Co. - Dec. 17, 1980 - M 86-42

Found - 32" Fir N.46°W., 15.3 ft. (Orig.)

14" Fir N.62°E., 22.0 ft. (Markham)

14" Fir N.24°E., 3.6 ft. (Orig.)

25" Fir S.58½°E., 43.6 ft. (Orig.)

Set 5/8" x 40" Iron rod and alum. cap.

New BTs- 14" Fir S.42°W., 58.3 ft.

25" Fir S.74°E., 39.7 ft.

David Edwards - For: Roseburg Resources Co. - Feb. 2011 - M162-12

Found - 5/8" dia. iron rod per M86-42.

32" fir N.46°W., 15.3'

14" fir stump N.62°E., 22.0'

27" fir S.74°E., 39.7'

17" fir S.42°W., 58.3'