

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & 1 of T31-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7797)

Set a stone 16x14x12 ins., 12" in the ground, for ¼ sec. cor. marked ¼ on W. face; from which
A Fir 33" dia., bears S.57¼°W., 25½ lks. dist. mkd. ¼ S BT
A Fir 5" dia., bears N.61¼°E., 23 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Aug. 2, 1960 - C.S. File 42/392-66

Corner determined by original BTs:
40" Fir snag S.57°W., 16.8 ft.
22" Fir N.61°E., 15.2 ft.
At corner point Found Stone mkd. ¼ and SET 3/4" x 30" I.P., from which
12" Maple N.44°E., 10.0 ft. mkd. ¼ S6 BT.
4" Fir N.75°E., 11.8 ft. mkd. ¼ S6 BT.
7" Fir S.58°E., 19.0 ft. mkd. ¼ S6 BT.
10" Laurel S.58°W., 18.5 ft. mkd. ¼ S1 R4W BT.
2" Fir N.49°W., 6.2 ft. mkd. ¼ S1 BT.

BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18138)

The ¼ sec. cor., perpetuated and recorded by Markham in 1960, monumented with the original stone, 16x14x12 ins., loosely set, projecting 10" above ground, no marks visible, (alongside of which is an iron pipe, 1/2" dia., firmly set, projecting 10" above ground,) from which the remains of the original bearing trees:

A Fir 30" dia., bears N.61¼°E., 23 lks. dist., with healed blaze.
A decayed Fir stump, size indeterminate, bears S.57¼°W., 25½ lks. dist., no marks visible.
and the remains of the bearing tree mkd. by Markham:
A root hole, bears N.44°E., 15 lks. dist. with down Maple alongside, 14" dia., with healed blaze.
A root hole bears S.58°E., 29 lks. dist. with down Fir alongside, 8" dia., with scribe marks ¼ S6 BT visible on partially healed blaze.
A Madrone 14" dia., bears S.59°W., 29 lks. dist. with scribe marks ¼ S1 BT visible on bark blaze.
A Fir 6" dia., bears N.49°W., 10 lks. dist. , with healed blaze.

At the corner point

(Cont. Next Page)

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & 1 of T31-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an stainless steel post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 31 S
R 4 W R 3 W
 ^{1/4}
S 1 | S 6
 1985

Deposit corner stone and iron pipe alongside, and white "DEEP-1" magnetic marker at base of stainless steel post.