

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 106700

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. for Sec. 31 only, T30-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 16 Page(s) 6781)

Set a stone 16x10x4 ins., 12" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Fir 11" dia., bears N.56½°E., 14½ lks. dist. mkd. ¼ S BT

A Fir 10" dia., bears S.57 3/4°W., 27½ lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - March 1963 - C.S. File 52/138-46

Found - Both orig. BTs and Stone, all as recorded.

Orig. 10" now 18" Fir S.58°W., 18.1 ft., shows good scar.

Orig. 11" now 16" Fir N.56°E., 9.5 ft., shows good scribing.

Set brass cap alongside cor. stone and marked:

County Surveyors Office

S ¼ S31 T30S R3W

1963

Fd. and Used in BLM resurvey by Wayne L. Rogers, Rick A. McMullen, Lance J. Bishop, Cadastral Surveyors, under Group #1217, surveyed Sept. 1984/April 1986 - (DCSO records Vol. 47 Page(s) 18128)

Fd. and Used in BLM Resurvey by Boyd W. Peterson and Dale T. Bedell, Cadastral Surveyors, Under Group #'s 1277 & 1315, Surveyed Sept. 1985/August 1986 - (DCSO records Vol. 48 Page(s) 18322)