

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #152, dated June 3, 1871, - (DCSO records Vol. 18 Page(s) 7693)

Set ¼ sec. post, from which
A Laurel 6" dia., bears N.45°W., 62 lks. dist.
A Fir 5" dia., bears S.40°W., 10 lks. dist.

George Wenderoth, Deputy County Surveyor - (Probably 1946 or 1947) - M 27-14

All signs of the corner gone. Set corner 2640 West of corner for 29, 30, 31 and 32.
Drive 1" Pipe for the corner, from which marked:
18" Fir bearing N.23°05'E., 8.0 ft. dist.
12" Fir bearing S.65°E., 20.8 ft. dist.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & Joe Brady, crew - Jan/Feb. 1966 - C.S. File 52/63-65

Found - Iron pipe as recorded.
18" Fir, dead, N.23°E., 8.0 ft. scribe visible "¼S
BT"
12" Fir, dead, S.65°E., 20.8 ft. scribe visible "¼S
BT"

Set Brass cap at cor. mkd: County Surveyors Office
T 31 S R 3 W
¼ S 30
S 31
1966

New BTs- 12" Laurel S.38½°E., 28.8 ft. scribed ¼ S31 CS BT.
13" D.Fir N.35°E., 65.0 ft. scribed ¼ S30 CS BT.

Douglas County Surveyors Office - Larry E. Monrean, Deputy - John Powell; T. Buley, crew - Dec. 29/30, 1981 - C.S. File 61/30-3

Condition report only
Found - Original monument not found.
NOTE: Inspection of the map in County Surveyor's file M 27-14 showing the method by which the following monuments were set, indicates that the proportioning procedure as defined by the BLM Surveying Manual was not used. The monuments are not at the most probably position of the ¼ corner. Due to their long standing and use in the area, it is necessary to leave the evidence found for future survey needs.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Found - 1" dia., Iron pipe.
A 1" dia. Iron pipe with an attached brass cap, 1966 cap, properly marked. Iron pipe is along westerly side of brass cap.
A Madrone 12" now 14" with well healed double blaze, bears S.41°E., 23.8 ft. (Rec. S.38½°E., 28.8 ft.) (Tag on tree notes distance as 123.8 ft.)
A D.Fir 13" now 15" with well healed double blaze, bears N.37½°E., 65.0 ft. (Rec. N.35°E.)

Carl Sweeden - For: Roseburg Resources Co. - March 2012 - M163-35

Found - 2½" DCSO 1966 BC along side 1" ID iron pipe 1947 Wenderoth BTs per CS 39/74:
Rotted remains of D.Fir BT, N.23°05'E., 8.0' (Measured to face of remains) rotted remains of D.Fir BT, S.65°E., 20.8' (measured to face of remains)
18" Madrone BT, S.38½"E., 28.8', healed blaze, 2 tags. 1966
21" D.Fir BT, N.34°E., 65.0', scar vis. tag. 1966
Set - 5/8" I.R. W/1½" alum cap "S30 ¼ S31 LS 2752", up 0.55' along side of found spike of no record S.65°19'19"E., 57.31' TO FD DCSO BC (S¼) AND 1" IP per C.S. 39/74 (Wenderoth)
Used the found BTs established in 1992 per LS 1086 with new measurements as noted:
13" D.Fir BT S.15°W., 18.2' to nail in bole, scar of dbl blaze vis., tagged
9" Madrone BT, S.65°W., 25.7' to nail in bole, partly open dbl blaze vis., tagged (LS 1086 washer in lower blaze)
45" Madrone BT, N.28°E., 14.05' to nail in bole, scribe vis. In dbl blaze, tagged (LS 1086 washer in lower blaze)
6" Madrone BT, N.48°W., 33.6' to nail in bole, scribe vis. in dbl blaze, tagged
All BTs have "MEDFORD RESOURCES CORP." tags as well.

Ron Quimby - Crew: N. Fromdahl, R. Olsen, R Heichel & R Vincent - 3/2018 - C.S. File 65/101-24

Found - 5/8" IR with 1½" alum cap (properly mkd)
15" D.Fir stump S.23°E., 18.2 ft. (Rec. S.15°W.)
10" Madrone S.65°W., 25.7 ft. vis. scribes
45" Madrone N.28°E., 14.05 ft. vis. scribes (tree dead) continued next page

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New -	6" madrone N.48°W., 33.6 ft vis. scribes (tree dead) 1" iron pipe along side - no brass cap. 10" Fir S.48°E., 14.6 ft. scribed ¼ S31 BT. 5" Fir N.16°E., 24.3 ft. X chest high. 19" Fir N.60°W., 22.8 ft. scribed ¼ S30 BT.
Note -	Compass decl. 15½°E.