

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 140240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by George Wenderoth - 1947 - C.S. File 39/74 & M 27-14

Point for corner located by intersection of the N-S and E-W center lines of section.

Set a 1" iron pipe, from which
14" Cedar N.4°50'W., 26.5 ft.
12" Fir S.58°45'E., 37.5 ft.

Carl Sweeden - For: Roseburg Resources Co. - March 2012 - M163-35

Set - 5/8" IR W/2" alum cap "C¼ S30 LS 2753 T31S R3W", up 0.70' along side of fd 2" alum cap (LS 1086) of no record

No trace of CS 39/74 1" IP by Wenderoth

Used found BTs established in 1992 per LS 1086 with new measurements as noted:

9" D.Fir BT S.70°W., 17.9' to nail in bole, dbl scar vis., tagged.

9.5" Madrone BT, N.32°W., 10.0' to nail in bole, scribe vis. In dbl blaze, tagged (LS 1086 washer in lower blaze)

7" Madrone BT, N.46°E 10.0' to nail in bole, scribe vis. in dbl blaze, tagged. (LS 1086 Washer in lower blaze)

13" Madrone BT, S.15°E., 26.5' to nail in bole, scribe vis. in dbl blaze, tagged

All BTs have "MEDFORD RESOURCES CORP" tags as well.

ALSO FD -

25" Cedar BT per CS 39/74, N.34°E., 9.25', scar vis.

Did not find fir BT at S.58°45'E., 37.5'