

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |
| Alias | Description |
| _____ | _____ |

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7763)

Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face, from which

A Fir 15" dia., bears N.71 3/4°E., 32½ lks. mkd. ¼ S BT.

A Fir 24" dia., bears S.14 3/4°E., 27½ lks. mkd. ¼ S BT.

George Wenderoth, Deputy Co. Surveyor - 1946/1947 - M 27-14

Find both original BTs, one dead.

I drove a 2' I.P. for the corner and marked a new BT:

10" Fir bearing S.24°35'W., 28.8 ft. (New BT)

28" Fir bearing N.79°05'E., 21.4 ft. (Orig. BT)

Carl Sweeden - For: Perpetual Forest Co - 3/2011 - M162-13

Found - 2" iron pipe in good condition

25" D.Fir BT now dead, S.14°E., 18.7', open w/scribe vis., tag

30 D.Fir BT stump, S.24°W 28.8', pitch seam vis. rotted fir BT laying down, N.79°E., 21.4 to root hole.

New BTs- 10" hemlock BT, N.3°E., 14.5', scribed S ¼ S19 BT", tag & nail in bole

14" I.Cedar BT, N.60°W., 9.7', scribed S ¼ S19 BT", tag & nail in bole

8" I.Cedar BT, S.5°E., 12.7', scribed S ¼ S30 BT", tag & nail in bole

12 D.Fir BT, N.78°E., 33.1', scribed S ¼ S30 BT", tag & nail in bole

FD. Ok by C. Sweeden, 3/2012 - M163-35