

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7766)

-----  
Set a post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which

A Laurel 6" dia., bears N.3½°W., 13¼ lks. dist. mkd. ¼ S BT.

A Fir 11" dia., bears S.20 ¾°E., 49 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -  
Wit: R.G. Boyd - Oct. 20, 1959 - C.S. File 42/392-32

-----  
Determined by O.B.T.:

15" Fir bears S.21°E., 32.4 ft., I chopped out and found scribe.

At corner point, Set ¾" x 30" Iron pipe, from which

30" Fir bears S.38°E., 42.0 ft. mkd. ¼ S19 T31S R3W BT.

9" Laurel bears N.50°E., 15.8 ft. mkd. ¼ S18 T31S R3W BT.

3" Fir bears N.34°E., 14.0 ft. mkd. ¼ S BT.

6" Laurel bears S.50°W., 8.0 ft. mkd. ¼ S19 BT.

Section line running West from ¼ corner 18 & 19 bears S.84°30'W.

Fd. OK, Feb. 1981 by H. Johnstone - M 86-42