

TOWNSHIP 31 RANGE 03 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7769)

A Fir 4" dia., which I mark ¼ S on N. face, for ¼ sec. cor., from which

A Laurel 5" dia., bears N.10½°W., 20 lks. dist. mkd. ¼ S BT.

A Laurel 7" dia., bears S.20½°E., 30 lks. dist. mkd. ¼ S BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd, O.A. Keatley - Nov. 16, 1959 - C.S. File 42/392-38

Determined by O.B.T.:

7" Laurel snag, N.20°E., 19.8 ft.

At corner point, found 20" Fir chopped out North face and found scribe, from which

16" Fir bears N.42°W., 18.0 ft. mkd. ¼ S7 BT.

8" Fir bears N.14°E., 6.0 ft. mkd. ¼ S7 X BT.

10" Fir bears N.40°E., 13.5 ft. mkd. ¼ S18 BT.

14" Fir bears S86°E., 14.5 ft. mkd. ¼ S18 BT.

Corner lies on very steep North face, approx. 120 ft. South of creek.

Section corner bears S82°45'W.

Section corner bears Due East.

Fd. OK Feb. 1981 by H. Johnstone - M 86-42